

MAINTEX



FACILITY SOLUTIONS

High Traffic

Product Information

- High gloss – wet look finish
- Durable, resists black marks and scuffs
- Easy to apply



FLOOR COATING AND FINISHING MATERIAL
AS TO SLIP RESISTANCE ONLY
1975



Floor Finish/Sealer Sellador y Acabado para Pisos

DESCRIPTION:

High Traffic Floor Finish/Sealer is one product for two jobs. High Traffic provides excellent durability, protection and wear for all types of flooring including: VCT, concrete, terrazzo, linoleum, unglazed ceramic and more. Several coats of this high solids finish achieve a long lasting “wet look” gloss which resists black marks and scuffing. Easy to apply and fast drying.

DIRECTIONS:

Restoration: 1- Completely remove old wax, finish and soil from floor surface following labeled directions on floor stripper 2- Ensure floor surface is clean, dry and free of residue. 3- Apply High Traffic onto floor with uniform, thin to medium coats with microfiber applicator or finish mop. 4- Allow drying before applying additional coats. Dry time is approximately 25-30 minutes per coat. Elevated temperatures and humidity may extend dry time.

Maintenance: 1- Sweep and damp mop floor periodically. 2- Clean floor using Maintex neutral cleaner. 3- Spray buff with Maintex “Spray & Gloss” or mop on Maintex “Reception” for renewed shine.

Recoating: 1- Dust mop or sweep floor. 2- Using a blue or green pad, top scrub the floor with Maintex “Spectrum”. 3- Apply 1-2 coats of “High Traffic” and allow drying.

DESCRIPCIÓN:

High Traffic Floor Finish/ Sealer es un producto para dos trabajos. High Traffic provee una durabilidad excelente y protección para todo tipo de pisos incluyendo, VCT, cemento, terrazo, linóleo, cerámica sin brillo y mucho más.

INSTRUCCIONES:

Restauración: 1- Completamente remueva toda la cera vieja, acabado y suciedad de la superficie del piso de acuerdo a las instrucciones del removedor de cera. 2-Asegurese que el piso este limpio, seco y libre de residuo. 3-Aplique capas delgadas a medianas de High Traffic en el piso con un aplicador de microfibra o un trapeador para acabados de piso. 4- Deje secar antes de aplicar capas adicionales. Tiempo de secar es 25-30 minutos por cada capa. Temperaturas elevadas y humedad puede extender el tiempo de resequedad.

Mantenimiento: 1- Barra y use un trapeador húmedo periódicamente. 2- Limpie el piso usando Maintex Neutral Cleaner. 3- Rocíe el pulidor de Maintex “Spray & Gloss” o trapee con Maintex “Reception” para un brillo renovado.

Nuevo Recubrimiento: 1- Barra el piso o use un trapeador seco. 2- Usando una almohadilla azul o verde, talle la superficie del piso con Maintex “Spectrum”. 3- Aplique 1-2 capas de “High Traffic” y deje secar.



1 Gallon
5 Gallons

127604
127605

TECHNICAL SPECS:

pH	8.5 - 9.5
Fragrance	Slight Ammonia
Color	White
Specific Gravity	1.02
VOC Content	N/A
Foam Characteristic	Low
Solubility in Water	Complete

See SDS for complete product information.

MAINTEX

www.maintex.com

13300 E. Nelson Avenue
City of Industry, CA 91746
(800) 446-1888

13575 Gregg Street
Poway, CA 92064
(800) 261-4456

Disclaimer This information is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Maintex Inc. assumes no responsibility for personal injury or property damage to the Vendee, Users or Third Parties caused by the material. Such Vendees or Users assume all risks associated with the use of this material. The contents of this document are subject to change without notice.